

Hygro-thermometer


Pocket hygro-thermometer w/probe



- ▲ SIMULTANEOUSLY TRIPLE DISPLAY TEMP./RH/EXTERNAL PROBE TEMPERATURE
- ▲ EASY-TO-READ BIG LCD DISPLAY
- ▲ DEW POINT & WET BULB TEMPERATURE DISPLAY. NO CHART REFERENCE IS NEEDED
- ▲ DESIGN WITH CAPACITANCE TYPE RH SENSOR TO GET ACCURATE AND QUICK READING
- ▲ EXTERNAL PROBE FOR CHECKING FOOD QUALITY & HVAC/R APPLICATIONS
- ▲ MAXIMUM / MINIMUM AND RESET FUNCTION
- ▲ TEMPERATURE UNIT °C/°F SELECTABLE
- ▲ HOLD FUNCTION TO FREEZE CURRENT READING
- ▲ EASY SELF-CALIBRATION BY OPTIONAL SALT KITS
- ▲ BATTERY LOW INDICATOR
- ▲ AUTO POWER OFF TIME FRAME SELECTABLE
- ▲ SLEEP MODE CAN BE DISABLED
- ▲ 8726 ADDITIONAL LY FEATURES AVG./TEMP. DIFFER/BACKLIGHT/ 99 MEMORIES/MEMORY STATISTIC/REAL TIME/IRDA OUTPUT
- ▲ 8716 FEATURES TEMP. DIFFER DISPLAY

Model	8706N	8706	8716	8726
Temp. range		-20~50°C		
Temp. resolution		0.1°C/°F		
Temp. accuracy		+/-0.6°C		
Humidity. range		0%RH~100%RH		
Humidity resolution		0.1%RH		
Humidity accuracy		+/-3%RH (at 25°C, 10~90%RH, others +/-5%RH)		
Dew point range	N/A	-78.7~50.0°C		
Wet bulb range	N/A	-21.6~50.0°C		
Response time		60 seconds typical		
External temp. range		-20~70°C		
Ext. temp. Accuracy		+/-0.6°C(-20~50°C), +/-1.2°C others		
LCD size (mm)		28(H)x33(W)		32(H)x39(W)
Storage temp.		-20~50°C		
Storage RH%		Humidity < 90%		
Dimension(mm)		48.4x178.5x24.7(H)		57x230x44(H)
Weight		~100g		~110g
Battery		AAA x 2pcs		AAA x 4pcs
Standard Package		Meter/Battery/Manual/Paper box		
Optional Accessory		External probe & calibration kits		

Optional



EXTERNAL TEMP. PROBE
 P/N: VZ87P6AZ
 COLOR: BLACK
 SIZE: 15CM PROBE W/HANDLE
 CABLE: 116CM W/2.5MM JACK



CAL. SALT BOTTLE
 P/N: VZ0033AZ1(33%)
 P/N: VZ0075AZ1(75%)
 FOR 8706N, 8706, 8716
 CALIBRATION USE



CAL. SALT BOTTLE
 P/N: VZHR33AZ (33%)
 P/N: VZHR75AZ (75%)
 FOR 8726 CALIBRATION
 PURPOSE.