

Hygro-thermometer



Pen type hygro-thermometer 8708/8709

- ▲ SIMULTANEOUSLY DISPLAY TEMPERATURE AND HUMIDITY
- ▲ EASY-TO-READ DUAL LCD DISPLAY
- ▲ DESIGN WITH CAPACITANCE TYPE RH SENSOR TO GET ACCURATE AND QUICK READING
- ▲ MAXIMUM / MINIMUM AND RESET FUNCTION
- ▲ TEMPERATURE UNIT °C/°F SELECTABLE
- ▲ HOLD FUNCTION TO FREEZE CURRENT READING
- ▲ EASY SELF-CALIBRATION BY OPTIONAL SALT KITS (8709 ONLY)
- ▲ ENTIRE LCD FLASH TO INDICATE LOW BATTERY STATUS
- ▲ SLEEP MODE CAN BE DISABLED
- ▲ POCKET CLIP DESIGN FOR EASY PORTABLE AROUND

Model	8708	8709
Temp. range	-10~50°C	-20~50°C
Temp. resolution	0.1°C/°F	0.1°C/°F
Temp. accuracy	+/-1°C	+/-1°C
Humidity. range	5%~95%RH	0%~100%RH
Humidity resolution	0.1%RH	0.1%RH
Humidity accuracy	+/-3%RH (at 25°C, 10~90%RH, others +/-5%RH)	
Dew point range	N/A	N/A
Wet bulb range	N/A	N/A
Response time	60 seconds typical	
Self calibration	N/A	YES
Battery life	>150 hours	
LCD size (mm)	18(H)x29(W)	
Storage temp.	-20~50°C	
Storage RH%	Humidity < 90%	
Dimension(mm)	175x42x16(H)	
Weight	~55g	
Battery	CR2032 x 1pc	
Standard Package	Meter/Battery/Manual/Paper box	
Optional Accessory	N/A	Calibration kits

Optional



CAL. SALT BOTTLE
P/N:VZ0033AZ1(33%)
P/N:VZ0075AZ1(75%)
FOR 8709
CALIBRATION USE