Combo Water Tester





Handheld IP67 Combo PH/COND./SALT/D.O. 8602

- **▲** Large LCD with multiple parameters measurement in one meter
- **▲** Easily measure pH/Conductivity or salinity/Dissolved oxygen in one meter by using different probes in turns
- ▲ Handheld fashion housing with IP67 waterproof design
- **▲** Auto temperature compensation
- Auto ranging for conductivity measurement
- Multiple points calibration: 3 points for pH, 1 point for D.O., 4 points for conductivity.
- **⚠** Manually altitude & salinity compensation for D.O. measurement
- **№** 99 points memories w/ recall function
- **▲** Low cost replacement probe
- **⚠** Temperature unit °C/°F is switchable
- A Powered by 4pcs AAA batteries
- **▲** 1 hour auto power off
- Application:
 - -excellent to use in fresh water aquafarm
 - -excellent to use in sea water aquafarm









8602

pH range	2.00~12.00
pH accuracy	+/-0.1
pH resolution	0.01
Cond. range	0~199.9, 0~1999uS/cm;0~19.99, 0~69.9mS/cm
Cond. accuracy	+/-1% F.S +/- 1 digit
Cond. resolution	0.1uS/cm, 1uS/cm;0.01mS/cm, 0.1mS/cm
Salinity range	0~10.00ppt; 0~42.0ppt(SEA WATER)
Salinity accuracy	+/-1% F.S +/- 1 digit
Salinity resolution	0.01 ppt, 0.1ppt
D.O. range	0.0~199.9% (0.0~30.0mg/L)
D.O. accuracy	+/-3% of F.S. +1 digit
D.O resolution	0.1
Temp. range	0~60.0°C
Temp. accuracy	+/-0.5°C
Temp. resolution	0.1
Compatible probe	PH PROBE, COND. PROBE AND D.O. PROBE COULD BE USED ON SAME METER IN TURNS
LCD size(mm)	32.5(H)x54(W)
Operating temp.&RH%	0~50°C, Humidity<80%
Storage temp.&RH%	0~60°C, Humidity < 90%
Dimension(mm)	169(L)x78.3(W)x43.4(H)
Weight	200g
Power	4PCS AAA Batteries
Standard Package	Meter/Manual/Carry case/Battery
Standard Probe	PH probe/Cond. Probe/D.O.Probe/D.O. Electrolyte/

to be included as standard)

Optional:

PH PROBE FOR # 8405/8602/8603

P/N:VZ861PAZ

COND. PROBE FOR # 8405/8602/8603 D.O. PROBE FOR # 8405/8602/8603 P/N: VZ841PAZ

MEMBRANE KIT FOR D.O. P/N: VZ84PAAZ FOR VZ841PAZ PROBE 5PCS/PACK

2 Membrane set/Cable clip (User can decide which probe