

Thermometer

Handheld RS232 Thermometer 8851/52/55/56



8851/8852



8855/8856

Optional



RS232 cable & software
P/N: VZRS232BN
USB cable & software
P/N: VZUSBAZM



Rubber holster / stand
P/N: VM68601HA, BLUE COLOR
P/N: VM68601HS+VM68601HS1
RED COLOR
P/N: VM68601HS11+VM68601HSA
GREY COLOR



K bead type thermocouple
P/N: VE60A000
Temp. range: -50~200°C
other custom made probe
: immersion, penetrate,
surface.....etc are available
upon request

- ▲ FASHION DESIGN AND THE MOST POPULAR LOW COST MULTIPLE TYPE THERMOCOUPLE MEASURING METER
- ▲ HOLD FUNCTION TO FREEZE CURRENT READING
- ▲ UNIT C/F IS SWITCHABLE
- ▲ NON SLEEP MODE FUNCTION AVAILABLE
- ▲ SUPER BIG LCD FOR EASY READING
- ▲ RS232 INTERFACE FOR PC DOWNLOAD
- ▲ DATA RECORDS STAMPED WITH REAL TIME CLOCK
- ▲ BACKLIGHT FOR DARK AREA OPERATION
- ▲ FEATURES OF EACH MODEL:
 - 8851: SINGLE INPUT &K/J/T PROBE COMPLIANT
 - 8852: DUAL INPUT &K/J/T PROBE COMPLIANT
 - 8855: SINGLE INPUT &K/J/T/R/S/E PROBE COMPLIANT
 - 8856: DUAL INPUT &K/J/T/R/S/E PROBE COMPLIANT

Model	8851	8852	8855	8856
K temp. Range & Accuracy (under 18~28°C ambient temp.)		-200~1370°C ; ±(0.1% rdg +0.7°C) -328~2498°F ; ±(0.1% rdg +1.4°F)		
Resolution	-200~650 °C/640~1370 °C -328~1000 °F/990~2498 °F		0.1°C/1°C 0.1°F/1°F	
J temp. Range & Accuracy (under 18~28°C ambient temp.)		-200~760°C ; ±(0.1% rdg +0.7°C) -328~1400°F ; ±(0.1% rdg +1.4°F)		
Resolution	-200~500 °C/490~760 °C -328~940 °F/930~1400 °F		0.1°C/1°C 0.1°F/1°F	
T temp. Range & Accuracy (under 18~28°C ambient temp.)		-200~390°C ; ±(0.1% rdg +0.7°C) -328~730°F ; ±(0.1% rdg +1.4°F)		
Resolution	-200~390 °C -328~730 °F		0.1°C 0.1°F	
R temp. Range & Accuracy (under 18~28°C ambient temp.)	N/A	N/A	0~1760°C ; ±(0.3% rdg +0.7°C) 32~3200°F ; ±(0.3% rdg +1.4°F)	
Resolution	0~1000 °C/990~1760 °C 32~1000 °F/990~3200 °F	N/A	0.1°C/1°C 0.1°F/1°F	
S temp. Range & Accuracy (under 18~28°C ambient temp.)	N/A	N/A	0~1760°C ; ±(0.3% rdg +0.7°C) 32~3200°F ; ±(0.3% rdg +1.4°F)	
Resolution	0~1000 °C/990~1760 °C 32~1000 °F/990~3200 °F	N/A	0.1°C/1°C 0.1°F/1°F	
E temp. Range & Accuracy (under 18~28°C ambient temp.)	N/A	N/A	-200~736°C ; ±(0.1% rdg +0.7°C) -328~1356°F ; ±(0.1% rdg +1.4°F)	
Resolution	-200~404 °C/370~736 °C -328~760 °F/710~1356 °F	N/A	0.1°C/1°C 0.1°F/1°F	
LCD size (mm, HxW)	30x51			
Operating temp.	0~50°C			
Operating RH%	Humidity < 80%			
Storage temp.	-20~50°C			
Storage RH%	Humidity < 90%			
Dimension(mm,LxWxT)	182x72x30			
Weight	~150g			
Battery	9V x 1pc or			
Standard Package	Meter, K bead thermocouple x1, battery, manual.			
Optional Accessory	K type thermocouple (custom made thermocouple is available upon request)			